ZAVIO

www.zavio.com

# F511E
# Firmware User Manual

# F511E Day/Night Box IP Camera

# Firmware User Manual

## - Contents -


**CHAPTER 1. MINIMUM SYSTEM REQUIREMENT ..... 2**

**CHAPTER 2. USING IP CAMERA VIA WEB BROWSER ..... 3**

**2.1 WINDOWS WEB BROWSER ..... 3**
**2.2 MAC WEB BROWSER ..... 5**

**CHAPTER 3. USING IP CAMERA VIA MOBILE PHONE ..... 8**

**3.1 USING IP CAMERA VIA IPHONE ..... 8**
**3.2 MOBILE PHONE VIEWING ..... 9**

**CHAPTER 4. MSN MESSENGER ..... 10**

**CHAPTER 5. CONFIGURATION OF MAIN MENU ..... 15**

**5.1 LIVE VIEW ..... 16**
**5.2 SETTING ..... 18**
**5.3 CLIENT SETTING ..... 19**
**5.4 IMAGE SETUP ..... 20**

**CHAPTER 6. SETTING-BASIC ..... 21**

**6.1 SYSTEM ..... 22**
**6.2 CAMERA ..... 27**
**6.3 NETWORK ..... 33**
**6.4 SECURITY ..... 47**

**CHAPTER 7. SETTING-ADVANCE ..... 50**

**7.1 FTP CLIENT ..... 51**
**7.2 SMTP ..... 59**
**7.3 HTTP EVENT ..... 69**
**7.4 ALARM OUTPUT ..... 76**
**7.5 SCHEDULE ..... 80**
**7.6 ALARM INPUT ..... 82**
**7.7 ALARM BUFFER ..... 83**
**7.8 MOTION DETECTION ..... 84**
**7.9 SYSTEM LOG ..... 86**

**CHAPTER 8. APPENDIX ..... 87**

# Firmware User Manual

## Chapter 1. Minimum System Requirement

We strongly recommend your computers follow our minimum requirements in order to use this IP-Camera normally. If computer level is lower than this, it might cause some problems.

| Item | Requirements |
|---|---|
| CPU | Pentium 4 1600MHz (or equivalent AMD) |
| Graphic Card | 64 MB RAM graphic cards(or equivalent on-board graphic cards) |
| RAM | 512 MB |
| Operating System | Windows 98, Windows ME (Please see Note)<br>Windows2000, 2003, XP, Vista, Mac OS X Leopard |
| Web Browser | Internet Explore 6 or later |

**Note:**

**1. If you are using Windows 98 or Windows ME, please install IP Installer before using WEB UI to ensure the system runs normally.**

**2. If you can't view the record video file, please install Xvid codec while installing Intelligent IP Installer. (For Windows 98, ME or 2000 server, the codec might not work properly. You'll need to download Xvid codec 1.0 from the internet.**

**3. Please always update the latest Windows component. (.Net Framework, Windows Media Player, Enhance ActiveX Security)**

# Chapter 2. Using IP Camera via Web Browser

## 2.1Windows Web Browser

**1. Start your web browser, and enter the IP address or host name of the IP camera in the Location / Address field of your browser.**

**Note :**

**If you only want to view the video without setting page, enter "http://<IP>/index2.htm" as your web URL.**

**2. Use the default account "admin" and default password "admin".**

**Note :**

**The default user name "admin" and the password are set at the factory for the administrator. You can change them in the Account Menu (Please check "Setting → Basic → Security → Account")**



**3. The monitor image will be displayed in your browser. In the far left side of main configuration are Setting, Client Setting, and Image Setup. For more details, you can check Chapter 5.2、Chapter 5.3 and Chapter 5.4.**



# 2.2 Mac Web Browser

**1. Click the Safari icon, and enter the IP address of the IP camera in the Location / Address field of your browser.**

**Note :**

**If you only want to view the video without setting page, enter "http://<IP>/index2.htm" as your web URL.**

**2. Use the default account “admin” and default password “admin”.**

**Note :**

**The default user name “admin” and the password are set at the factory for the administrator. You can change them in the Account Menu (Please check “Setting → Basic → Security → Account”)**

Safari File Edit View History Bookmarks Window Help
Thu 4:50 PM
Apple
To view this page, you need to log in to area "P5110 Megapixel IR Pan/Tilt IP Camera" on 10.0.0.105.
Your password will be sent in the clear.
Name:
Password:
Remember this password in my keychain
Cancel
Log In
Store
Support
The world's thinnest and lightest 17-inch notebook.
Introducing the new 17-inch MacBook Pro.
Featuring a breakthrough 8-hour battery.
Watch the video
Watch the keynote

**3. The monitor image will be displayed in your browser. In the far left side of main configuration are Setting, Client Setting, and Image Setup. For more details, you can check Chapter 5.2、Chapter 5.3 and Chapter 5.4.**



# Chapter 3. Using IP Camera via Mobile Phone

## 3.1 Using IP Camera via iPhone

**You can use Zavio Web User Interface via iPhone. Please follow the setting process below. Then you can use Zavio web UI via iPhone.**

**1. Select Safari function**




**2. Enter IP address in your web link.**

**3. Type name and password. Default value is admin / admin. Then click Login In**




**4. The Zavio User Interface and live image will show up in the middle of screen.**

**Note: It will show continuous snapshots not a real time video streaming. Therefore, the recording feature is disabled.**

# 3.2 Mobile Phone Viewing

To use IP cameras via mobile phones, please make sure your RTSP is set to "On" (Default is "On"). To change the settings of IP cameras, **Please check "Settings → Basic → Camera → General."**

## 1. 3G Mobile Phone Streaming Viewing

For 3G mobile phone viewing, type " **rtsp://<IP>:<PORT>/video.3gp** " into your 3G Streaming Link. **<IP>** is the Public IP address of your IP camera; **<PORT>** is the RTSP port of your IP camera (Default value is 554.) Example: rtsp://100.10.10.1:554/video.3gp

**Note: You can also use RTSP clients (RealPlayer, VLC, QuickTime Player…etc.) to view RTSP streaming, just type in "rtsp://<IP>:<PORT>/video.3gp" as the Player URL**

## 2. 2.5G Mobile Phone WAP Viewing

For 2.5G mobile phone viewing, type " **<IP>/mobile.wml** " into your 2.5G WAP Browser. **<IP>** is the Public IP address of your IP camera.

## 3. 2.5G Mobile Phone Browser Viewing

For 2.5G mobile phone viewing, type " **<IP>/mobile.htm** " into your 2.5G Web Browser. **<IP>** is the Public IP address of your IP camera.

# Chapter 4. MSN Messenger

Please see the following steps to set up the Messenger function.

**1.** You can download MSN software freely and create a **new MSN account** (**camera at home**) to use Microsoft Live Messenger.

**2.**Go to Setting→Basic→Network→Messenger , set the Messenger to "ON" . Then, **login in new account and password (Camera at home).**




**3.** Choose "On" at the option of **IP Notification. If this feature switches On**, camera will send IP notification to the users who are allowed.

**4.** Choose "On" at the option of **Privacy.** If you can choose "On" at the privacy option, you can set an allow list.




5. Use your account to login in the Messenger software. Then, add the new MSN account (**Camera at home** )

**6.** The Camera at home will show up with its Public IP and Private IP if the option of IP Notification is “On”. **( You can enter “Ping” to show up with Public IP and Private IP. )**

**7.** Click on the small **camera icon** . Then, choose “View a new contact's webcam”.

**8.** The IP Camera will accept your invitation; the live video will show up in the right screen after few seconds.


camera at home - Conversation
File Edit Actions Tools Help
camera at home
http://220.133.2.196/ <ivy_zavio@hotmail.com>
Never give out your password or credit card number in an instant message conversation.
camera at home says:
My Public IP: 220.133.2.196
URL: http://220.133.2.196/
Wired-Private IP: 10.0.0.94
URL: http://10.0.0.94/
You have invited camera at home to start sending webcam. Please wait for a response or Cancel (Alt+Q) the pending invitation.
camera at home has accepted your invitation to start sending webcam.
Send
Search
Connection established.
Get accessories

**9.** Click **Action** button and choose **Start control panel** to use control panel.




**10.** The dialog box will show up with "This application is not part if Window Live Message……." **Tick** the box of "Don't show me this again" and **click OK**


Windows Live Messenger
This application is not part of Windows Live Messenger. MSN and Microsoft do not accept liability for this application if it causes damage to your computer or results in a violation of your privacy.
Are you sure you want to open this application?
Don't show me this again
OK
Cancel

**11.** The IP Camera will accept your invitation to start **Control Panel.**


camera at home - Conversation
File Edit Actions Tools Help
camera at home
http://220.133.2.196/ <ivy_zavio@hotmail.com>
Control Panel
Wired-Private IP: 10.0.0.94
URL: http://10.0.0.94/
You have invited camera at home to start sending webcam. Please wait for a response or Cancel (Alt+Q) the pending invitation.
camera at home has accepted your invitation to start sending webcam.
You have invited camera at home to start Control Panel. Please wait for a response or Cancel (Alt+Q) the pending invitation.
camera at home has accepted your invitation to start Control Panel.
Get accessories
Send
Search
Connection established.

**12.** You can click **Camera icon** **to snapshot** then the picture will send to you immediately.


camera at home - Conversation
File Edit Actions Tools Help
camera at home
http://220.133.2.196/ <ivy_zavio@hotmail.com>
Snapshot
camera at home has accepted your invitation to start Control Panel.
camera at home has stopped viewing webcam with you.
You have invited camera at home to start sending webcam. Please wait for a response or Cancel (Alt+Q) the pending invitation.
camera at home has accepted your invitation to start sending webcam.
camera at home sends:
snapshot20080916114744.jpg (7 KB)
Double-click here to start transfer
Accept(Alt+C) Save As...(Alt+S) Decline(Alt+D)
Get accessories
Send
Search
Connection established.

**13.** You can click **paint palette icon** showing up with tool bar to set up image. Then, you can use the tool bar to optimize video **Brightness** **, Contrast** **, Saturation** **and Hue** **.** After the adjustment of all setting, you can still click 

to make the setting back to the original setting.


camera at home - Conversation
File Edit Actions Tools Help
camera at home
http://220.133.2.196/ <ivy_zavio@hotmail.com>
Wired-Private IP: 10.0.0.94
URL: http://10.0.0.94/
You have invited camera at home to start sending webcam. Please wait for a response or Cancel (Alt+Q) the pending invitation.
camera at home has accepted your invitation to start sending webcam.
You have invited camera at home to start Control Panel. Please wait for a response or Cancel (Alt+Q) the pending invitation.
camera at home has accepted your invitation to start Control Panel.
Send
Search
Connection established.
Get accessories
Control Panel
50
35
50
50
Default
Image Setup

# Chapter 5. Configuration of Main Menu

**In the far left side of main configuration are Setting, Client Setting, Image Setup. For more details, you can check Chapter 5.2、Chapter 5.3、Chapter 5.4.**




**In your right hand side, you can use Live View in your main Browser. There are Snapshot, Zoom and Audio and Video Play four different function. You can see more details as follow.**

# 5.1 Live View

## A. Snapshot

You can capture a still image shot by the camera and save it in your computer.

| Symbols | Meaning |
|---|---|
| | a snapshot window will appear |
| **Save** | to save the picture in your computer |
| **Close** | to return to the view page |
| | full Screen |

## B. Zoom in / out the image via the monitor window




- Click to display the digital zoom in window.
- Pull the to adjust the digital zoom range, and it will be showed on the above window.
- You can use the left click of your mouse to move the to any where on the window.

# C. Video play buttons

| Symbols | Meaning |
|---|---|
| | Pause the current video |
| | Play the video |
| | Stop the current video |
| | Record the current video |

**Note:**
**Concerning the recording storage requirement of your hard disk, please refer to the CHAPTER 8. APPENDIX / B. Storage Requirement Table.**

# D. Audio buttons

| Symbols | Meaning | Note |
|---|---|---|
| | Speakers turned on | **mean the speakers of your computer are turned on to transmit the sounds from the connected IP camera(s)** |
| | Speakers turned off | |
| | Microphone turned on | **mean you can broadcast to the connected IP camera(s) via the Ethernet using your microphone** |
| | Microphone turned off | |
| | Volume control bar | |

# 5.2 Setting




This function is only for the Administrator. Click this button to get into the **Basic** and **Advance settings** menu.




**Click Basic folder, there are four sub-folders including System, Camera, Network, and Security. Fore more information, you can see Chapter 6.1、Chapter 6.2、Chapter 6.3 and Chapter 6.4.**

**Click Advance folder, there are four sub-folders including FTP Client, SMTP, HTTP event, Alarm output, Schedule, Alarm input, Motion Detection, and System Log. Fore more information, you can see Chapter 7.1、Chapter 7.2、Chapter 7.3、Chapter 7.4、Chapter 7.5、Chapter 7.6、Chapter 7.7、Chapter 7.8、Chapter 7.9.**

# 5.3 Client Setting

This function is only for the client.

Click this button to control **Mode, View Size, Protocol,** and **Video Buffer.**

## 5.3.1 Mode

Click the pull-down box to choose between MPEG4 and MJPEG video compression mode.

MJPEG streaming is unavailable if RTSP mode is “On.”

**(Please check Setting → Basic → Camera → General)**

**Note：MJPEG streaming is unavailable if RTSP mode is On.**

## 5.3.2 View Size

Select the desired display image resolution to 640X480 or 320X240.

## 5.3.3 Protocol

Select the transferring protocol from TCP, UDP, HTTP and Multicast.

## 5.3.4 Video Buffer

Turn the Video Buffer function ON / OFF. The Video Buffer function makes the streaming more smoothly in unsteady network environment, but might cause a little delay in live viewing.

# 5.4 Image Setup

You can use the tool bar to optimize video **Brightness, Contrast, Saturation** and **Hue.**



## 5.4.1 Brightness

The higher value the brightness is, the brighter the image is.

## 5.4.2 Contrast

The contrast is a measure of a display system, defined as the ratio of white to black that the system is capable of producing. The higher value the contrast is, the more delicate of color you can have.

## 5.4.3 Saturation

The saturation of a color is determined by a combination of light intensity and how much it is distributed across the spectrum of different wavelengths. The higher value the saturation is, the more colorful the image will be.

## 5.4.4 Hue

Hue is one of the three main attributes of perceived color, affected by different wavelength of color. With higher value of hue, color will be much more vivid.

## 5.4.5 Default




After the adjustment of all setting, you can still click Default to make the setting back to the original setting.

# Chapter 6. Setting-Basic

Click the folder of **Basic** to display the sub folders including **System, Camera, Network, and Security.**



# 6.1 System

Click the folder of **System** to display the sub-folders including **Information, Date / Time, and Initialize.**



# 6.1.1 Information

The Information page provides the product factory information which includes **Product Name, Firmware Version and Web Version.**

# 6.1.2 Date / Time

The Date/ Time page displays all options of time setting.




➢ **Current date / time**: This displays the current date and time of this IP Camera.

➢ **PC clock**: This displays the date and time of the monitoring PC clock.

➢ **Date / Time format**: You can click the pull down box to select different time display formats.

➢ **Adjust**: You can select one of those four adjusting modes for your IP Camera.

- ●Keep current setting: Select this mode to keep the current date and time of this IP Camera.
- ●Synchronize: Select this mode to keep the date and time of this IP Camera is the same as the monitoring PC.
- ●Manual setting: Select this mode to adjust manually the date and time of this IP Camera.
- ●Synchronize with NTP: Specify the NTP server name and the Refresh Interval to synchronize the date and time of this IP Camera with those of the time server, known as the NTP server.

➢ **Time Zone**: You can select the Time Zone of the format from Greenwich Mean Time. The time will display the same as the current date / time option.

**Note:**

**The NTP server (Network Time Protocol) is the time server which is an Internet standard protocol built on the top of TCP / IP. This assures accurate synchronization to the millisecond of computer clock times in a network of computers.**



ZAVIO

# 6.1.3 Initialize




➢ **Reboot**: Click this bottom to reboot this IP Camera. A confirmation dialogue will appear and then click "OK" to process. It takes two minutes to reboot this IP Camera.

➢ **Factory Default**: Click this bottom to reset this IP Camera to the factory default setting. A confirmation dialogue will appear and then click "OK" to process. The network indicator on this IP Camera will start to blink. This IP Camera will reboot automatically after completing adjustments to the default setting. Don't turn off this IP Camera until the device reboots.

➢ **Backup Setting**: You can save the setting data of this IP Camera into a file. Click "Save" and follow the instructions on the browser to save the setting data file to your specified location.

➢ **Restore Setting**: Download the saved setting data of this IP Camera. Click "Browse" and select saved file. Click "OK" and this IP Camera is adjusted according to the loaded data and then restarted.

➢ **Firmware Update**: Upgrade the device software. Click "Browse" and select the file for upgrading. A confirmation dialogue will appear. Click "OK" to start upgrading. This IP Camera will reboot upon completion.

**Note:**

**Use only upgrade files that are special for this IP Camera. Otherwise problems may occur. Don't turn off the IP Camera power or disconnect the network until the upgrading is completed.**

➢ **Upload Language Pack**: Upgrade the device language pack. Click “Browse” and select the file for upgrading. A confirmation dialogue will appear. Click “OK” to start upgrading. The upgrade is applied immediately. The default language is “English.”

# 6.2 Camera

Click the folder of **Camera** to display the sub folders including **General, MPEG4 and MJPEG.**



# 6.2.1 General




➢ **RTSP** : Switch On / Off

**Note: RTSP (Real Time Streaming Protocol) is a protocol for use in streaming media system which allows clients to remotely control a streaming video server. RTSP is supports by most of the media clients such as Real Player, QuickTime and VLC...etc.**

➢ **Image Rotate**: You can mirror or flip the display screen.

➢ **Night Mode**: You can choose Auto / Off. **If you choose Auto option**, the camera will adjust automatically to perform well when the environment is dark

➢ **Lighting**: You can choose the environment among 50 Hz, 60 Hz , and Outdoor.

➢ **White Balance**: You can choose the white balance to Auto, Florescent, Incandescent and Black & White.

➢ **IR**: You can turn LEDs light On / Off and Auto. **If you select Auto mode,** you can adjust threshold for LEDs Auto-On and Auto-Off respectively. In the right hand side of threshold, if the tool bar is closer to the right, the LEDs will auto-on easily in the dark environment. Conversely, in the left hand side of threshold, if the tool bar is more approach to the left, the LEDs will auto-off easily in the bright environment.

➢ **Overlay**:

- ●Text Overlay: You can see some information on the display screen which includes Date / Time and user-defined text. Also, you can change the background color.
- ●Privacy Mask: You can cover a specific area of the video image.

# 6.2.2MPEG4

## A. Computer View




➢ **RTSP (if RTSP mode is On, please check "Setting → Basic → Camera → General ")**

- ●RTSP Port: Specify the transmission port number of RTSP streaming. The default value is 8554.
- ●Viewer Authentication: If the viewer authentication is On, the users will be requested to key-in username and password when viewing through RTSP.

➢ **RTP (if RTSP mode is On, please check "Basic→ Camera → General")**

- ●Unicast Streaming Video / Audio Port Range: Specify the transmission port range of RTP streaming video. RTP will select a port randomly from the range.
- ●Multicast Streaming (If it is ON)
- ●Multicast Address: Specify the multicast server address.
- ●Video / Audio Port: Specify the transmission port number of the video data. Specify an even number from 1024 to 65534.
- ●Time to Live: Set the maximum TTL that multicast can pass through.

➢ **Image Size**: Specify the image size when the network camera transmits. You can choose among 640 x 480, 320 x 240, and 160 x 120.

➢ **Frame Rate**: Set the frame rate of the MPEG4 image. You can choose values from 5, 10, 15, 20, 25, and 30 fps. The unit "fps" stands for "frames per second".

➢ **Quality:**

- ●Auto: The quality and bitratee will be adjusted automatically according to the frame rate.
- ●Fixed Quality: You can select the value of quality among Medium, Good, Delicate

and Excellent.

●Fixed Bitrate: Set the bitrate of MPEG4 image transmission for a line. You can select the values from 64, 128, 256, 384, 512, 768, 1024, 1280, 1536, and 2048 kbps.




**➢ MPEG4 view port (if RTSP mode is Off, please check "Basic → Camera → General")**

●Unicast Streaming **Video / Audio Port Number:** Specify the transmission port number of the video data. It is initially set to 8090. You can specify an even number from 1024 to 65534. If you change the setting of Video / Audio Port Number, the setting of Video / **Audio Port Number (SSL) will change automatically.**

**Note:**

**Concerning how to select the suitable image quality for Fixed Quality or Fixed Bitrate, please refer to the CHAPTER 8. APPENDIX / A. Frame-rate & Bitrate Table.**

# B. Mobile View




➢ **RTSP (if RTSP mode is On, please check "Setting → Basic → Camera → General")**

- ●RTSP Port: Specify the transmission port number of RTSP streaming. The default value is 554.

➢ **RTP (if RTSP mode is On, please check "Setting → Basic → Camera → General")**

- ●Unicast Streaming Video / Audio Port Range: Specify the transmission port range of RTP streaming video. RTP will select a port randomly from the range.
- ●Multicast Streaming (If it is On)
  - ✓ Multicast Address: Specify the multicast server address.
  - ✓ Video / Audio Port: Specify the transmission port number of the video data. It is initially set to 10000 and 11000. Specify an even number from 1024 to 65534.
  - ✓ Time to Live: Set the maximum TTL that multicast can pass through.

➢ **Image Size**: The image size of Mobile View is fixed at 160 x 120.

➢ **Frame Rate**: Set the frame rate of the MPEG4 image. You can choose values from 5, 10, 15, 20 fps. The unit "fps" stands for "frames sent per second".

➢ **Quality:**

- ●Fixed Bitrate: Set the bitrate of MPEG4 image transmission for a line. You can select the value from 64, 32, 16 kbps.

**Note:**

**Concerning how to select the suitable image quality for Fixed Quality or Fixed Bitrate, please refer to the CHAPTER 8. APPENDIX / A. Frame-rate & Bitrate Table.**

# 6.2.3 MJPEG




➢ **MJPEG Viewer Port( If RTSP is off, please check "Setting → Basic → Camera → General"):**

- Unicast Streaming Video / Audio Port Number: Specify the transmission port number of the video data. It is initially set to 8070. You can specify an even number from 1024 to 65534. If you change the setting of Video / Audio Port Number, the setting of Video / **Audio Port Number (SSL) will change automatically.**

➢ **Image Size**: Specify the image size when the network camera transmits. You can choose among 640 x 480, 320 x 240, and 160 x 120.

➢ **Frame Rate**: Set the frame rate of the MJPEG image. You can choose values from 5, 10, 15 fps. The unit "fps" stands for "frames per second".

➢ **Quality:**

- Auto: The quality will be automatically decided.
- Fixed Quality: You can select the value of quality among Medium, Standard, Good, Delicate and Excellent.

**Note:**

**Concerning how to select the suitable image quality for Fixed Quality or Fixed Bitrate, please refer to the CHAPTER 8. APPENDIX / A. Frame-rate & Bitrate Table.**

# 6.3 Network

Click the folder of **Network** to display the sub folders including **Information, PPPoE, DDNS, UPnP, Bonjour, IP Notification, and Messenger.**



# 6.3.1 Information

Display the MAC address of the device.




➢ **Obtain an IP address automatically (DHCP)**: If a DHCP server is installed on the network, to select this while the IP address is assigned by the DHCP server.

➢ **Obtain DNS server address automatically**: Select this to obtain the address of DNS server automatically.




➢ **Use the following IP address**: Select this when the fixed IP address is set.

- ●IP address: Enter the IP address of the device.
- ●Subnet mask: Enter the subnet mask.
- ●Default gateway: Enter the default gateway.

➢ **Use the following DNS server address**: Select this when you set the fixed address as the IP address of DNS server.

- ●Primary DNS server: Enter the IP address of the primary DNS server.
- ●Secondary DNS server: Enter the IP address of the secondary DNS server, if necessary.

➢ **HTTP port number**: Select **80** in general situations. If you want to use a port number other than **80**, select the text box and enter a port number between 1024 and 65535.

- ●When you have set the HTTP port number to a number other than 80 on the Network setting page or in the Setup Program, access the device by typing the IP address of the device on the web browser as follows: Example: when HTTP port number is set to 2000 http://192.168.1.100:2000/

**Note: The IP Camera needs to be rebooted after it finishes changing the network setting completely**.

**Note: If you connect the IP Camera with your computer directly, the default network domain of camera is 192.168.1.xx**

# 6.3.2 PPPoE (Point-to-Point Protocol over Ethernet)

If your ISP provides Dynamic IP with authentication by username and password, type all PPPoE information in this part. When you use the PPPoE function, you need to turn on the DDNS or IP Notification function at same time.




➢ **IP address**: The IP address obtained at the PPPoE connecting with network.

➢ **User ID**: Enter the user ID for authentication necessary for PPPoE connections. Type it up to 64 characters.

➢ **Password**: Enter the password for authentication necessary for PPPoE connections. Type it up to 32 characters.

➢ **Re-type password**: Re-type the password to confirm.

➢ **Obtain DNS server address automatically**: Select this to obtain the address of DNS server automatically.




➢ **Use the following DNS server address**: Select this when you set the fixed address as the IP address of DNS server.

●Primary DNS server: Enter the IP address of the primary DNS server.

●Secondary DNS server: Enter the IP address of the secondary DNS server.

**Note :**

**1. PPPoE (Point-to-Point Protocol over Ethernet): PPPoE is a network protocol for encapsulating Point-to-Point Protocol frames insider Ethernet frames. PPPoE connection is used mainly with ADSL service where individual users connect to the ADSL transceiver (modem) over Ethernet work. It also widely used in XDSL (digital affiliate line such as ADSL, VDSL or SDSL)**

**2. The IP Camera needs to be rebooted after it finishes changing the network completely.**

**3. The IP Camera with Intelligent IP Installer can't be founded after turning on the PPPoE and reboot.**

# 6.3.3 DDNS (Dynamic DNS)

DDNS is a system which allows the domain name data held in a name server to be updated in real time. The most common use for DDNS is allowing an internet domain name to be assigned to a computer with a varying / dynamic IP Address. This makes it possible for other sites on the internet to establish connection to the machine without needing to track the IP Address themselves.




➢ **Server name**: Choose the DDNS Server from the list.

➢ **User ID**: Enter the user ID for authentication necessary for DDNS connections. Type it up to 64 characters.

➢ **Password**: Enter the password for authentication necessary for DDNS connections. Type it up to 32 characters.

➢ **Re-type password**: Re-type the password to confirm.

➢ **Host name**: Enter the host name that is registered to the DDNS server.

**Note :**

**How to apply DDNS username and Host name??**

You can apply DDNS username and Host name by the following steps:

**1. Login http://www.dyndns.org, click the Create Account**




**2. Input all information and follow step by step with DynDNS**


DynDNS Account Registration - Windows Internet Explorer
DynDNS.com › Dynect › DynTLD › Corporate
DynDNS
User: Pass: Login
Lost Password? - Create Account
About Services Account Support News
My Account
Create Account
Login
Lost Password?
Search
Search
Create Your DynDNS Account
Please complete the form to create your free DynDNS Account.
User Information
Username:
Email Address:
Instructions to activate your account will be sent to the email address provided.
Confirm Email Address:
Password:
Your password needs to be more than 5 characters and cannot be the same as your username. Do not choose a password that is a common word, or can otherwise be easily guessed.
Confirm Password:
About You (optional)
Providing this information will help us to better understand our customers, and tailor future offerings more accurately to your needs. Thanks for your help!
How did you hear about us:
We do not sell your account information to anyone, including your email address.
Details:
Terms of Service
Please read the accepatable use policy (AUP) and accept it prior to creating your account. Also acknowledge that you may only

## 3. Login with new account and click Account → My Hosts → Add Host Services




## 4. Type domain in the Hostname field and select sub-domain



**5. After type information, check your DDNS service.**




**6. Type your DDNS User ID, Password and Host name in Setting → Network → DDNS. After completing setting, reboot IP Camera.**



# 6.3.4 UPnP (Universal Plug and Play)

If you have a Router to access to internet and the Router supports UPnP IGD function, you need to turn on the UPnP Port Forwarding function.




➢ **HTTP port**: Enter the HTTP port number and default HTTP port is 80.

➢ **SSL port:** Enter the SSL port number and default SSL port is 443.

➢ **MPEG4 viewer port**: Enter the MPEG4 viewer port number and default MPEG4 viewer port is 8090.

➢ **MPEG4 viewer port (SSL)**: Enter the MPEG4 SSL viewer port and default is 8091.

➢ **MJPEG viewer port:** Enter the MJPEG viewer port number and default MJPEG viewer port is 8070.

➢ **MJPEG viewer port (SSL)**: Enter the MPEG4 SSL viewer port and default is 8071.

➢ **MPEG4 RTSP port:** Enter the MPEG4 RTSP port, default value is 8050 for computer view, 8030 for mobile view.

**Note :**

**UPnP (Universal Plug and Play): UPnP is a set of computer network protocol. It allows devices to connect seamlessly and simplify the implementation of networks in the home and corporate environments. The device supports UPnP which is enabled by default. The device will be automatically detected and a new icon will be added to "My Network Place" if it also enables on your computer. It provides Port Forwarding for opening a port in a router or firewall in a private network in order to let a party from the outside world contact a inside user.**



ZAVIO

# 6.3.5 Bonjour

Bonjour, also known as zero-configuration networking, enables automatic discovery of computers, devices, and services on IP networks. Bonjour uses industry standard IP protocols to allow devices to automatically discover each other without the need to enter IP addresses or configure DNS servers.




➢ **Device Name**: Enter Device Name you wish.

**Note: How to use Bonjour in your Windows Browser UI? Please check the link below:**

**http://www.apple.com/support/downloads/bonjourforwindows.html**

# 6.3.6 IP Notification

When network notify type is set to “ON”, you can send an e-mail notification of the completion of the network setting.




➢ **Notify Type**: You can select the notify type among DHCP, Static IP, and PPPoE.

➢ **SMTP Server Name**: Type the SMTP server name up to 64 characters, or the IP address of the SMTP server.

➢ **SMTP Server Port**: You can set port number from 1~65535 according to your mail server. The default value is 25.

●Security setting: Tick SSL box if the mail server you use has security restriction.

**Note:**

**If you use g-mail as your mail server, you should set 587 as your port number and tick SSL box.**

➢ **Authentication**: Select the authentication required when you send an email.

●Off: Select if no authentication is necessary when an email is sent.

●On: When authentication is necessary an e-mail is sent, there are **SMPT, POP before SMPT or both** three options.




➢ **Authentication**: Select the authentication required when you send an email.

- ●Off: Select if no authentication is necessary when an email is sent.
- ●On: When authentication is necessary an e-mail is sent, there are **SMPT, POP before SMPT or both** three options.

➢ **SMTP:** Select if SMTP authentication is necessary when an e-mail is sent.

➢ **POP before SMTP**: Select if POP before SMTP authentication is necessary when an e-mail is sent.

- ●**POP server name**: It is necessary when the **POP before SMTP** is selected in **Authentication**. Type the POP (receiving mail) server name up to 64 characters, or type the IP address of the POP server. This setting is necessary when the SMTP server which sends e-mails performs authentication using the POP user account.
- ●**User name, Password**: Type the user name and Password of the user who has the mail account. This setting is necessary when the SMTP server which sends e-mails performs authentication.

➢ **Recipient e-mail address**: Type the recipient e-Mail address up to 64 characters. You can specify up to three recipient E-mail addresses.

➢ **Administrator e-mail address**: Type the Administrator e-Mail address up to 64 characters. This address is used for reply mail and sending system messages from the SMTP server.

➢ **Subject**: Type the subject/title of the e-Mail up to 64 characters. With respect to mail which is sent according to the IP notification.

➢ **Message**: Type the text of the E-mail up to 384 characters. Default value provides network information including IP, Port, MAC, Model, Firmware Version and Web Version.

# 6.3.7 Messenger

Messenger function provide an easy-connect feature. User can easy to know what camera's private and public IP address is.




➢ **Protocol**: support MSN only.

➢ **Login Account**: Camera will use this account to login MSN server. This MSN account should be applied form http://www.msn.com.

➢ **Password**: password for this msn account.

➢ **Re-type password**: re-type password to double confirm.

➢ **Alias**: This alias will display on MSN like the following which display in red frame.

➢ **Port range**: Camera will select one port from this port range for video transmission.

➢ **IP Notification**: Switch the IP notification On / Off. **If this feature switches On**, camera will send IP notification to the users who are allowed.

➢ **Privacy**: Switch privacy On / Off. **When privacy turns on**, only those users in allowed list can access the camera.

➢ **User**: Input to this blank to edit allow list.

➢ **Allow list**: When privacy turns on, only those users in allow list can access the camera.

# 6.4 Security

Click the folder of **Security** to display the sub folders including **Account and HTTPS.**



# 6.4.1 Account

The device fault account and password setting is “admin / admin”. That means everyone who knows IP address can access the device including all configuration. It is necessary to assign a password if the device is intended to be accessed by others.




➢ **User name**: Set a user name between 4-16 characters.

➢ **Password**: Set a password between 4-16 characters.

➢ **Re-type Password**: Re-type the password to confirm.

➢ **Viewer Mode**: Set the user mode among Admin, Operator, and Viewer. Different viewer mode has different limits of authority.

- The Admin mode has all authority of configuration.
- The Operator mode can not only view the Live View but also control the PTZ (apply in speed dome).
- The Viewer mode only can view the Live View.

➢ **Viewer Authentication**: Allows any viewer direct access to Live View.

# 6.4.2 HTTPS

**HTTPS** is a URI scheme used to indicate a secure HTTP connection. It is syntactically identical to the http:// scheme normally used for accessing resources using HTTP. Using an https: //URL/ with a different default TCP port (443) and an additional encryption / authentication layer between the HTTP and TCP. You can use the IP camera through HTTPS easily by using https:// instead of http://.




➢ **Create & Install**: Create a self-signed certificate for HTTPS to recognize.

➢ **Installed Certificate**: Display or remove the properties of the installed certificate.

➢ **HTTPS Connection Policy**: Set HTTPS connection policy for different level of users.

➢ To use the HTTPS encryption, please set up "**Create self-signed certificate**" for the first time you use the HTTPS function, and then set up the connection policy for different users.




**Note:**

**When enable HTTPS with RTSP on mode, the IP Camera only protect the setting such as username and password and do not protect video and audio. When enable HTTPS with RTSP off mode, the IP Camera will protect all setting including video and audio.**

# Chapter 7. Setting-Advance

Click the folder of **Advance** to display the sub folders including **FTP client, SMTP, HTTP event, Alarm output, Schedule, Alarm input, Alarm buffer, Motion detection and System Log.**



# 7.1 FTP Client

Use this menu to set up for capturing and sending images to an FTP server. By using FTP client function, you can send the **image and video file** which has been shot and recorded linked with the external sensor input or with the built-in motion detection function to FTP server. FTP client setting menu is composed of two tabs, **General**, **Alarm sending** and **Periodical sending**.



# 7.1.1 General

Select "**On"** when you use FTP function. The FTP client setting page appears.
Select "**Off",** when you do not wish to use the FTP client function.

**Note:**

**The frame rate and operability on the main viewer may decrease while a file is being transmitted by the FTP client function.**




- **FTP server name**: Type the FTP server name to upload still images up to 64 characters, or the IP address of the FTP server.
- **User name**: Type the user name for the FTP server.
- **Password**: Type the password for the FTP server.
- **Retype password**: To confirm the password, type the same characters as you typed in the Password box.
- **Passive mode**: Set whether you use the passive mode of FTP server or not when connecting to FTP server. Select **On** to connect to FTP server using the passive mode.
- **Attached file type**: You can choose the attached file in **JPEG** or **MPEG4** type.

# 7.1.2 Alarm sending

Set to forward the **image and audio file** to the specified FTP server linked with the alarm detection by the external sensor input or by the built-in motion detection function. Select **On** to send the image file to FTP server linked with the alarm detection.




➢ **Remote Path**: Type the path to the destination in FTP server up to 64 characters.

➢ **Image File Name**: Type the file name you want to assign to the images when sending to the FTP server. You can use up to 10 alphanumeric characters, - (hyphen) and _ (underscore) for naming.

➢ **Suffix**: Select a suffix to add to the file name

- **Date & time**: The date & time suffix is added to the Image file name. The date/time suffix consists of lower two-digits of year (2 digits), month (2 digits), date (2 digits), hour (2 digits), minute (2 digits), second (2 digits), and consecutive number (2 digits), thus 14-digit number is added to the file name.
- **Sequence number**: A consecutive number of 10 digits between 0000000001 and 4294967295 and two fixed digits 00 is added to the Image file name.
- **Sequence number clear**: Click **Clear** and the suffix of the sequence number returns to 1.

➢ **Alarm**

●**Motion Detection**: Click it on for using **Motion Detection** function as a sensor. You can set motion detection function at the motion detection function page.







**Note:** You can set motion detection at motion detection page. **(Please go "Setting → Advance →Motion detection → Setting") For more details, you can check Chapter 7.8.**

- **Use Alarm Buffer**：Select **Use alarm buffer** when you forward the image and video of before and after the alarm detection (pre-alarm, post-alarm). If you do not select it, only the image of the moment of the alarm detection is forwarded. Click **Alarm buffer** to display the Alarm buffer setting menu.




**Note:** You can set the alarm buffer function at alarm buffer page. **(Please go "Setting → Advance → Alarm buffer → Setting"). For more details, you can check Chapter 7.7.**

●**Alarm Input**: Select the connected alarm. **Sensor input1**: The external sensor which is connected to sensor input1 of the alarm input.

**Note:** You can set the alarm input function at alarm input page. **(Please go "Setting → Advance → Alarm input → Setting"). For more details, you can check Chapter 7.6.**

➢ **Effective period**: Set the period when the periodical sending is effective.

●**Always**: The periodical sending is always effective.

●**Schedule**: You can specify the period when the periodical sending is effective in the Schedule setting in the other section.

**Note:** You can set schedule function at schedule page. **(Please go "Setting → Advance → Schedule → Setting") For more details, you can check Chapter 7.5.**


Schedule
Schedule - Windows Internet Explorer
http://10.0.0.47/schedule.htm
Schedule selection FTP - Alarm
Mon Start time 00 : 00 - End time 24 : 00
Tue Start time 00 : 00 - End time 24 : 00
Wed Start time 00 : 00 - End time 24 : 00
Thu Start time 00 : 00 - End time 24 : 00
Fri Start time 00 : 00 - End time 24 : 00
Sat Start time 00 : 00 - End time 24 : 00
Sun Start time 00 : 00 - End time 24 : 00
Use the same time schedule every day.
OK
Cancel
Done
Internet
100%

# 7.1.3 Periodical sending

You can set to send an image file to FTP server periodically by selecting **On** to send the image file to FTP server linked with setting period.




➢ **Image file name**: Type the file name of the image sent by SMTP up to 10 alphanumeric characters, - (hyphen) and _ (under score).

➢ **Suffix**: Select a suffix to be added to the file name sent by SMTP.

- **None**: The name of the sent file will be the Image file name.
- **Date & time**: The date & time suffix is added to the Image file name. The date & time suffix consists of lower two-digits of year (2 digits), month (2 digits), date (2 digits), hour (2 digits), minute (2 digits) and second (2 digits), and consecutive number (2 digits), thus 14-digit number is added to the file name.
- **Sequence number**: A **consecutive** number is added to the Image file name.
- **Sequence number clear**: Click **Clear** and the suffix of the sequence number returns to 1.

➢ **Interval**: Set the periodical sending is effective interval. Min value is 1 min and Max value is 24 hour.

➢ **Effective period**: Set the period when the periodical sending is effective.

●**Always**: The periodical sending is always effective.

●**Schedule**: You can specify the period when the periodical sending is effective in the Schedule setting in the other section.

**Note:** You can set schedule function at schedule page. **(Please go "Setting → Advance → Schedule → Setting") For more details, you can check Chapter 7.5.**


Schedule - Windows Internet Explorer
http://10.0.0.47/schedule.htm
Schedule selection
FTP - Alarm
Mon Start time 00 : 00 - End time 24 : 00
Tue Start time 00 : 00 - End time 24 : 00
Wed Start time 00 : 00 - End time 24 : 00
Thu Start time 00 : 00 - End time 24 : 00
Fri Start time 00 : 00 - End time 24 : 00
Sat Start time 00 : 00 - End time 24 : 00
Sun Start time 00 : 00 - End time 24 : 00
Use the same time schedule every day.
OK
Cancel
Done
Internet
100%

# 7.2 SMTP

Set the SMTP menu when you want to send an image via e-mail. By using Mail (SMTP) function, you can send a mail with attached **image and video** which has been shot linked with the external sensor input or with the built-in motion detection function. The image file can also be sent periodically. E-Mail (SMTP) setting menu is composed of three tabs, **General**, **Alarm sending** and **Periodical sending**.



# 7.2.1 General

Select **On** when you use the SMTP function. The common setting options are displayed below. Select **Off,** if you do not wish to use the e-Mail (SMTP) function.

**Note :**

**The Setting of general part will be the same as the setting of IP Notification (Please check "Setting → Basic → Network → IP Notification")**




➢ **SMTP server name**: Type the SMTP server name up to 64 characters, or the IP address of the SMTP server.

➢ **SMTP Server Port**: You can set port number from 1~65535 according to your mail server. The default value is 25.

●**Security setting**: Tick SSL box if the mail server you use has security restriction.

**Note:**

**If you use g-mail as your mail server, you should set 587 as your port number and tick SSL box.**

➢ **Authentication**: Select the authentication required when you send an email.

●Off: Select if no authentication is necessary when an email is sent.

●On: When authentication is necessary an e-mail is sent, select one of the authentication methods from the followings.




➢ **Authentication**: Select the authentication required when you send an email.

- ●Off: Select if no authentication is necessary when an email is sent.
- ●On: When authentication is necessary an e-mail is sent, select one of the authentication methods from the followings.

➢ **SMTP**: Select if SMTP authentication is necessary when an e-mail is sent.

➢ **POP before SMTP**: Select if POP before SMTP authentication is necessary when an e-mail is sent.

**Note：When you set to On, be sure to select either or both SMTP or / and POP before SMTP.**

- ●**POP server name**: It is necessary when the **POP before SMTP** is selected in **Authentication**. Type the POP (receiving mail) server name up to 64 characters, or type the IP address of the POP server. This setting is necessary when the SMTP server which sends e-mails performs authentication using the POP user account.
- ●**User name, Password**: Type the user name and Password of the user who has the mail account. This setting is necessary when the SMTP server which sends e-mails performs authentication.

➢ **Recipient e-mail address**: Type the recipient e-Mail address up to 64 characters. You can specify up to three recipient E-mail addresses.

➢ **Administrator e-mail address**: Type the Administrator e-Mail address up to 64 characters. This address is used for reply mail and sending system messages from the SMTP server.

➢ **Subject**: Type the subject/title of the e-Mail up to 64 characters. With respect to mail which is sent according to the alarm detection when **Alarm sending** of the alarm tab is set

to **On**, the characters standing for the sensor type added to the subject.

- **Message**: Type the text of the E-mail up to 384 characters. (A line break is equivalent to 2 characters.)

# 7.2.2 Alarm sending

Set to send the mail with connection to the alarm detection by the external sensor input or by the built-in motion detection function. Select On to send the image and file to SMTP server linked with the alarm detection.




➢ **Alarm sending**: Select **On** to set to send mail with connection to the alarm detection.

➢ **File attachment**: Set whether an image file is attached to the mail sent or not. When **On** is selected, the image file made by the settings below is attached. When **Off** is selected, only the message is sent.

➢ **Image file name**: Type the file name you want to assign to the image to attach a mail. You can use up to 10 alphanumeric, - (hyphen) and _ (underscore) for naming.

➢ **Suffix**: Select a suffix to add to the file name

- **Date & time**: The date & time suffix is added to the Image file name. The date/time suffix consists of lower two-digits of year (2 digits), month (2 digits), date (2 digits), hour (2 digits), minute (2 digits), second (2 digits), and consecutive number (2 digits), thus 14-digit number is added to the file name.
- **Sequence number**: A consecutive number of 10 digits between 0000000001 and 4294967295 and two fixed digits 00 is added to the Image file name.
- **Sequence number clear**: Click **Clear** and the suffix of the sequence number returns to 1.




➢ **Alarm**

●**Motion Detection**: Click it on for using **Motion Detection** function as a sensor. You can set motion detection function at the motion detection function page.







**Note:** You can set motion detection at motion detection page. **(Please go "Setting → Advance → Motion detection → Setting") For more details, you can check Chapter 7.8.**

●**Use Alarm Buffer**：Select **Use alarm buffer** when you forward the image and video of before and after the alarm detection (pre-alarm, post-alarm). If you do not select it, only the image of the moment of the alarm detection is forwarded. Click **Alarm buffer** to display the Alarm buffer setting menu.




**Note:** You can set the alarm buffer function at alarm buffer page. **(Please go "Setting → Advance → Alarm buffer → Setting"). For more details, you can check Chapter 7.7.**

●**Alarm Input**: Select the connected alarm. **Sensor input1**: The external sensor which is connected to sensor input1 of the alarm input.

**Note:** You can set the alarm input function at alarm input page. **(Please go "Setting → Advance → Alarm input → Setting"). For more details, you can check Chapter 7.6.**

➢ **Effective period**: Set the period when the periodical sending is effective.

- **Always**: The periodical sending is always effective.
- **Schedule**: You can specify the period when the periodical sending is effective in the Schedule setting in the other section.

**Note:** You can set schedule function at schedule page. **(Please go "Setting → Advance → Schedule → Setting") For more details, you can check Chapter 7.5.**


Schedule - Windows Internet Explorer
http://10.0.0.47/schedule.htm
Schedule selection
FTP - Alarm
Mon Start time 00 : 00 - End time 24 : 00
Tue Start time 00 : 00 - End time 24 : 00
Wed Start time 00 : 00 - End time 24 : 00
Thu Start time 00 : 00 - End time 24 : 00
Fri Start time 00 : 00 - End time 24 : 00
Sat Start time 00 : 00 - End time 24 : 00
Sun Start time 00 : 00 - End time 24 : 00
Use the same time schedule every day.
OK
Cancel
Done
Internet
100%

# 7.2.3 Periodical sending

You can set to send an image file by SMTP server periodically by selecting **On** to send the image file by SMTP server linked with setting period.




- **Image file name**: Type the file name of the image sent by SMTP up to 10 alphanumeric characters, - (hyphen) and _ (under score).
- **Suffix**: Select a suffix to be added to the file name sent by SMTP.
  - **None**: The name of the sent file will be the Image file name.
  - **Date & time**: The date & time suffix is added to the Image file name. The date & time suffix consists of lower two-digits of year (2 digits), month (2 digits), date (2 digits), hour (2 digits), minute (2 digits) and second (2 digits), and consecutive number (2 digits), thus 14-digit number is added to the file name.
  - **Sequence number**: A consecutive number is added to the Image file name.
  - **Sequence number clear**: Click **Clear** and the suffix of the sequence number returns to 1.
- **Interval**: Set the periodical sending is effective interval. Min value is 30 min and Max value is 24 hour.

➢ **Effective period**: Set the period when the periodical sending is effective.

●**Always**: The periodical sending is always effective.

●**Schedule**: You can specify the period when the periodical sending is effective in the schedule setting in the other section. **Please check "Setting → Basic → Advance → Schedule → Setting."**

**Note:** You can set schedule function at schedule page. **(Please go "Setting → Advance → Schedule → Setting") For more details, you can check Chapter 7.5.**


Schedule - Windows Internet Explorer
http://10.0.0.47/schedule.htm
Schedule selection
FTP - Alarm
Mon Start time 00 : 00 - End time 24 : 00
Tue Start time 00 : 00 - End time 24 : 00
Wed Start time 00 : 00 - End time 24 : 00
Thu Start time 00 : 00 - End time 24 : 00
Fri Start time 00 : 00 - End time 24 : 00
Sat Start time 00 : 00 - End time 24 : 00
Sun Start time 00 : 00 - End time 24 : 00
Use the same time schedule every day.
OK
Cancel
Done
Internet
100%

# 7.3 HTTP event

Use this menu to set up for capturing and sending images to an HTTP server. By using HTTP client function, you can send the image file and audio file which has been shot and recorded linked with the external sensor input or with the built-in motion detection function to HTTP server. HTTP client setting menu is composed of two tabs, **General** and **Alarm sending.**



# 7.3.1 General




➢ **HTTP event**: Set up the HTTP server URL, port, User ID, Password, and Proxy Server settings.




**For example:**

**URL: 192.168.1.7/cgi-bin/operator/ptzset**

**Note: The setting of URL should be the same as CGI**

# 7.3.2 Alarm sending

Set to send the mail with connection to the alarm detection by the external sensor input or by the built-in motion detection function. Select **On** to send the image and audio file to HTTP server linked with the alarm detection.




**Alarm sending**: Select **On** to set to send mail with connection to the alarm detection.

➢ **Alarm**

●**Motion detection**、**Use alarm buffer**、 **Alarm input**

➢ **Effective period**: Set the period when the periodical sending is effective.

●**Always**: The periodical sending is always effective.

●**Schedule**: You can specify the period when the periodical sending is effective in the schedule setting in the other section.

**Note:**

**You can set schedule function at schedule page. (Please go "Setting → Advance → Schedule → Setting") For more details, you can check Chapter 7.5.**

➢ **Alarm**

●**Motion Detection**: Click it on for using **Motion Detection** function as a sensor. You can set motion detection function at the motion detection function page.







**Note: You can set motion detection at motion detection page. (Please go "Setting → Advance → Motion detection → Setting") For more details, you can check Chapter 7.8.**

**Note： Motion Detection works only when the MPEG4 function is On.**




- ✓ **Parameter:** the parameter of CGI (defined in URL of HTTP → General) is from your target device. For example, move=down.
- ✓ **Message:** message will show up in the form of Message = PTZ down. If your target device didn't support the parameter of message, you can't see the message. So you can just take the message as a note. For example: PTZ down.

●**Use Alarm Buffer**: Select **Use alarm buffer** when you forward the image / audio of before and after the alarm detection (pre-alarm, post-alarm). If you do not select it, only the image of the moment of the alarm detection is forwarded. Click **Alarm buffer** to display the Alarm buffer setting menu.




**Note:**

**You can set the alarm buffer function at alarm buffer page. (Please go "Setting → Advance → Alarm buffer → Setting") For more details, you can check Chapter 7.7.**




- ✓ **Parameter:** the parameter of CGI (defined in URL of HTTP→General) is from your target device. For example, move=down.
- ✓ **Message:** message will show up in the form of Message = PTZ down. If your target device didn't support the parameter of message, you can't see the message. So you can just take the message as a note. For example: PTZ down.

●**Alarm Input:** Select the connected alarm. **Sensor input1**: The external sensor which is connected to sensor input1 of the alarm input.




**Note:**

**You can set the alarm input function at alarm input page. (Please go "Setting → Advance → Alarm input → Setting") For more details, you can check Chapter 7.6.**




- ✓ **Parameter:** the parameter of CGI (defined in URL of HTTP→General) is from your target device. For example, move=down.
- ✓ **Message:** message will show up in the form of Message = PTZ down. If your target device didn't support the parameter of message, you can't see the message. So you can just take the message as a note. For example: PTZ down.

➢ **Effective period**: Set the period when the periodical sending is effective.

- **Always**: The periodical sending is always effective.
- **Schedule**: You can specify the period when the periodical sending is effective in the Schedule setting in the other section.

**Note:** You can set schedule function at schedule page. **(Please go "Setting → Advance → Schedule → Setting") For more details, you can check Chapter 7.5.**


Schedule - Windows Internet Explorer
http://10.0.0.47/schedule.htm
Schedule selection
FTP - Alarm
Mon Start time 00 : 00 - End time 24 : 00
Tue Start time 00 : 00 - End time 24 : 00
Wed Start time 00 : 00 - End time 24 : 00
Thu Start time 00 : 00 - End time 24 : 00
Fri Start time 00 : 00 - End time 24 : 00
Sat Start time 00 : 00 - End time 24 : 00
Sun Start time 00 : 00 - End time 24 : 00
Use the same time schedule every day.
OK
Cancel
Done
Internet
100%

# 7.4 Alarm Output

When you click **Alarm output** on the Advance mode menu, the Alarm output setting menu appears. You can set in this menu to control the alarm out of I / O port on the rear of the device linked to the alarm detection and the timer.



# 7.4.1 Setting




**Alarm output**: To activate the Alarm output function, select **On**. When you do not use the Alarm output function, select **Off**.

- **Digital output**: Select High signal output and Low signal output as your alarm.
- **Trigger condition**: Select the mode of the Alarm output function. You can choose "**Alarm" or "Timer".**
- **Alarm:** Controls alarm output by synchronizing with an external sensor input or the built-in activity detection function.
  - **Motion Detection**: Click it on for using **Motion Detection** function as a sensor. You can set motion detection function at the motion detection function page.






**Note:**

**You can set motion detection at motion detection page. (Please go "Setting → Advance → Motion detection → Setting"). For more details, you can check Chapter 7.8.**

**Note：Motion Detection works only when the Video mode is set to MPEG4 and the Cropping is set to Off.**

- **Use Alarm Buffer**: Select **Use alarm buffer** when you forward the image / audio of before and after the alarm detection (pre-alarm, post-alarm). If you do not select it, only the image of the moment of the alarm detection is forwarded. Click **Alarm buffer** to display the Alarm buffer setting menu.




**Note:**

**You can set the alarm buffer function at alarm buffer page. (Please go "Setting → Advance → Alarm buffer →Setting ") For more details, you can check Chapter 7.7.**

- **Alarm Input:** Select the connected alarm. **Sensor input1**: The external sensor which is connected to sensor input1 of the alarm input.

**Note:**

**You can set the alarm input function at alarm input page. (Please go "Setting →Advance →Alarm input → Setting"). For more details, you can check Chapter 7.6.**

➢ **Alarm duration**: There are up to 60 second options to choose for alarm duration interval.

➢ **Effective period**: Set the period when the periodical sending is effective.

●**Always:** The periodical sending is always effective.

●**Schedule**: You can specify the period when the periodical sending is effective in the Schedule setting in the other section.

**Note:**

**You can set schedule function at schedule page. (Please go "Setting → Advance → Schedule → Setting") For more details, you can check Chapter 7.5.**


Schedule - Windows Internet Explorer
http://10.0.0.47/schedule.htm
Schedule selection
FTP - Alarm
Mon Start time 00 : 00 - End time 24 : 00
Tue Start time 00 : 00 - End time 24 : 00
Wed Start time 00 : 00 - End time 24 : 00
Thu Start time 00 : 00 - End time 24 : 00
Fri Start time 00 : 00 - End time 24 : 00
Sat Start time 00 : 00 - End time 24 : 00
Sun Start time 00 : 00 - End time 24 : 00
Use the same time schedule every day.
OK
Cancel
Done
Internet
100%

# 7.5 Schedule

When you click **Schedule** on the Advance mode menu, the Schedule setting menu appears. This is the same menu as the setting menu which is displayed when you click **Schedule** to set Effective period and Schedule in **FTP** client setting menu, e-Mail (**SMTP**) setting menu, Alarm out setting menu and so on.

**Example: When setting e-Mail (SMTP) (the alarm sending) in the Schedule setting menu.**



# 7.5.1 Setting


HOME
SETTING
BASIC
Advance
FTP client
SMTP
HTTP event
Alarm output
Schedule
Setting
Alarm input
Alarm buffer
Motion detection
System Log
Schedule selection
FTP - Alarm
Mon Start time 00 : 00 - End time 24 : 00
Tue Start time 00 : 00 - End time 24 : 00
Wed Start time 00 : 00 - End time 24 : 00
Thu Start time 00 : 00 - End time 24 : 00
Fri Start time 00 : 00 - End time 24 : 00
Sat Start time 00 : 00 - End time 24 : 00
Sun Start time 00 : 00 - End time 24 : 00
Use the same time schedule every day.
OK
Cancel

➢ **Schedule Selection**: Select the list box to specify the schedule you want to set.

- **●FTP -Alarm**
- **●FTP - Periodical**
- **●e-Mail (SMTP) -Alarm**
- **●e-Mail (SMTP) -Periodical**
- **●HTTP event -Alarm**
- **●Alarm output- Alarm**
- **●Alarm output- Timer**

➢ **Mon (Monday) to Sun (Sunday)**: The time period on the right of the checked day is the effective period of the schedule.

➢ **Start time, End time**: Specify the **Start time** and the **End time**.

➢ **Use the same time schedule every day:** When this is checked, the **Start time** and **End time** set to **Mon** (Monday) are applied to all days. In this case, the **Start time** and **End time** of the other days than **Mon** (Monday) cannot be input.

# 7.6 Alarm Input

When you click **Alarm Input** on the Advance mode menu, the Alarm input setting menu appears. You can set in this menu to control the external alarm input of I / O port on the rear of the device linked to **FTP, SMTP, and HTTP sending function.**




# 7.6.1 Setting

**Sensor input 1**: Click it on for using external sensor which is connected to sensor input1 of the camera I / O port.

- **Trigger condition**: Select High signal output and Low signal output as your alarm.
- **Camera move**: Pull down the window to select the camera preset position.

# 7.7 Alarm buffer

You can set the Pre-alarm image and audio (the image and audio before the alarm detection) and the Post - alarm image and audio. These can be set when **Alarm sending** FTP client setting menu or Image memory setting menu is set to **On**, and besides when **Use alarm buffer** is selected.




# 7.7.1 Setting

**Alarm buffer**: To activate the Alarm buffer function, select **On**. The basic setting options are displayed below. When you do not use the Alarm output function, select **Off**.

➢ **Recording capacity**

●**Pre-alarm period**: Display the maximum recording capacity of image/audio before the alarm detection.

●**Post-alarm period**: Display the maximum recording capacity of image/audio after the alarm detection.

➢ **Recording time**: Set the recording time for the Pre-alarm image/audio and Post alarm image/audio.

●**Pre alarm period**: Type it with recording time of the image/audio before the alarm detection.

●**Post alarm period**: Type it with recording time of the image/audio after the alarm detection.

**Note：The value of Recording capacity differs depending on Image size, Bitrate (for MPEG4) and Image quality (for MPEG4 and MJPEG) in the camera setting menu.**

# 7.8 Motion Detection

There are three Motion Detection functions as sensors to set for different detecting zones. Each one has Threshold and Sensitivity inputs which you can adjust to specific zone sequentially. Motion Detection function can support to FTP, SMTP and Alarm output for capturing and sending images or starting alarm output.



# 7.8.1 Setting




➢ **Threshold**: It means the extent which the alarm will be triggered.

➢ **Sensitivity:** It means that how often the sensor will scan the image different. The higher sensitivity it is and the more frequently it scans.

●**Motion Detection 1**: Click it on for using **Motion Detection 1** function as a sensor. You can adjust and move the detecting zone by using mouse.
●**Motion Detection 2**: Click it on for using **Motion Detection 2** function as a sensor. You can adjust and move the detecting zone by using mouse.
●**Motion Detection 3**: Click it on for using **Motion Detection 3** function as a sensor. You can adjust and move the detecting zone by using mouse.

# 7.9 System Log

The System Log function allows users to review any changes and events happened. The system starts logging automatically after started.




## 7.9.1 Setting

- **Enable remote log**: Enables user to send the log data to a specified log server.

# CHAPTER 8. APPENDIX

**APPENDIX A – FRAME RATE & BIT RATE TABLE**

This chapter provides tables that help you to optimize your IP camera with your network environment. Base on your network upload environment to choose the best Image-Quality setting. For example, if the network environment is ADSL 256Kb(upload) / 2Mb(download), the most fluent Image-Quality needs to set up under 256 Kb situation.

## A.1 MPEG4 @ 30fps / kbps

| Quality | 640*480 | 320*240 | 160*120 |
|---|---|---|---|
| Excellent | **1000** | **300** | **90** |
| Detailed | **400** | **150** | **50** |
| Good | **300** | **100** | **30** |
| Standard | **250** | **70** | **25** |
| Medium | **250** | **55** | **20** |

## A.2 MPEG4 / kbps, fps

| Image-Size | Bitrate Setting | Frame-Rate Setting | Current Bitrate | Current Frame-Rate |
|---|---|---|---|---|
| 640*480 | 2048 | 30 | **1800** | **26** |
| 640*480 | 2048 | 15 | **2200** | **16** |
| 640*480 | 1536 | 30 | **1500** | **30** |
| 640*480 | 1536 | 15 | **1700** | **16** |
| 640*480 | 1024 | 30 | **1000** | **30** |
| 640*480 | 1024 | 15 | **1000** | **16** |
| 640*480 | 512 | 30 | **500** | **30** |
| 640*480 | 512 | 15 | **600** | **16** |
| 320*240 | 1536 | 30 | **1500** | **30** |
| 320*240 | 1536 | 15 | **1600** | **16** |
| 320*240 | 1024 | 30 | **1000** | **30** |
| 320*240 | 1024 | 15 | **1000** | **16** |
| 320*240 | 512 | 30 | **550** | **30** |
| 320*240 | 512 | 15 | **600** | **16** |
| 160*120 | 1024 | 30 | **950** | **30** |
| 160*120 | 1024 | 15 | **750** | **16** |
| 160*120 | 512 | 30 | **500** | **30** |
| 160*120 | 512 | 15 | **50** | **16** |
| 160*120 | 128 | 30 | **130** | **30** |
| 160*120 | 128 | 15 | **140** | **16** |

## A.3 MJPEG @ 15fps / kbps

| Quality | 640*480 | 320*240 | 160*120 |
|---|---|---|---|
| Excellent | **4000** | **1500** | **600** |
| Detailed | **2400** | **900** | **400** |
| Good | **1600** | **650** | **300** |
| Standard | **1300** | **500** | **240** |
| Medium | **900** | **350** | **170** |

## A.4 MJPEG / kbps, fps

| Image-Size | Quality Setting | Frame-Rate Setting | Current Bitrate | Current Frame-Rate |
|---|---|---|---|---|
| 640*480 | Excellent | 15 | **4000** | **13** |
| 640*480 | Excellent | 5 | **1600** | **5** |
| 640*480 | Good | 15 | **1600** | **13** |
| 640*480 | Good | 5 | **650** | **5** |
| 640*480 | Medium | 15 | **900** | **14** |
| 640*480 | Medium | 5 | **360** | **5** |
| 320*240 | Excellent | 15 | **1500** | **13** |
| 320*240 | Excellent | 5 | **550** | **5** |
| 320*240 | Good | 15 | **650** | **13** |
| 320*240 | Good | 5 | **260** | **5** |
| 320*240 | Medium | 15 | **350** | **13** |
| 160*120 | Medium | 5 | **130** | **5** |
| 160*120 | Excellent | 15 | **600** | **13** |
| 160*120 | Excellent | 5 | **230** | **5** |
| 160*120 | Good | 15 | **300** | **13** |
| 160*120 | Good | 5 | **115** | **5** |
| 160*120 | Medium | 15 | **170** | **13** |
| 160*120 | Medium | 5 | **65** | **5** |

**APPENDIX B – STORAGE REQUIREMENT TABLE**

This chapter provides tables that help you set your recording storage system.
Please refer to the following table to find out the capability for recording into your hard disk.

## B.1 MPEG4 Storage Requirement GB / channel / day @ 30fps

| Quality | 640*480 | 320*240 | 160*120 |
|---|---|---|---|
| Excellent | **10.5** | **3.2** | **0.9** |
| Detailed | **4.2** | **1.6** | **0.5** |
| Good | **3.2** | **1.1** | **0.3** |
| Standard | **2.6** | **0.7** | **0.3** |
| Medium | **2.6** | **0.6** | **0.2** |

## B.2 MPEG4 Storage Requirement GB / channel / day @ 15fps

| Quality | 640*480 | 320*240 | 160*120 |
|---|---|---|---|
| Excellent | **5.3** | **1.6** | **0.4** |
| Detailed | **2.1** | **0.8** | **0.3** |
| Good | **1.6** | **0.6** | **0.2** |
| Standard | **1.3** | **0.4** | **0.1** |
| Medium | **1.3** | **0.3** | **0.1** |

## B.3 MPEG4 Storage Requirement GB / channel / day

| Image-Size | Bitrate Setting | Frame-Rate Setting | Current Bitrate |
|---|---|---|---|
| 640*480 | 2048 | 30 | **23.0** |
| 640*480 | 2048 | 15 | **22.2** |
| 640*480 | 1536 | 30 | **18.5** |
| 640*480 | 1536 | 15 | **17.9** |
| 640*480 | 1024 | 30 | **10.5** |
| 640*480 | 1024 | 15 | **10.5** |
| 640*480 | 512 | 30 | **5.3** |
| 640*480 | 512 | 15 | **6.3** |
| 320*240 | 1536 | 30 | **15.8** |
| 320*240 | 1536 | 15 | **16.9** |
| 320*240 | 1024 | 30 | **10.5** |
| 320*240 | 1024 | 15 | **10.5** |
| 320*240 | 512 | 30 | **5.8** |
| 320*240 | 512 | 15 | **6.3** |
| 160*120 | 1024 | 30 | **10.0** |
| 160*120 | 1024 | 15 | **7.9** |
| 160*120 | 512 | 30 | **5.3** |
| 160*120 | 512 | 15 | **0.5** |
| 160*120 | 128 | 30 | **1.4** |
| 160*120 | 128 | 15 | **1.5** |